

TECHNICAL SPECIFICATION

Downlight fixtures for CFL - GL210



Technical data

- Nominal voltage: 230V / 50Hz
- Lamp power: 2X10W; 2X13W; 2X18W; 2X26W
- Lampholder designation: G24q
- Type of light source (not included commercial kit): 2pcs Compact fluorescent lamps PLC-2P (TC-D) or PLC-4P (TC-DEL)
- Operating mode:
 - Electronic control gear for PLC-4P type lamp (not included commercial kit)
 - Magnetic control gear for PLC-2P type lamp (not included commercial kit)
- Body material: Sheet steel with aluminium ring
- Diffuser: Glass with matt dots
- Reflector: Aluminium mirror
- Type of Installation: Recessed mounting for indoor use
- Body color: white, satin nickel
- Dust and humidity protection level: IP20
- Protection against electric shock: I
- Protection against ignition and fire: Class F


Areas of application

- Modern Residential Buildings
- Commercial buildings
- Offices
- Hotels
- Recreation facilities

Product benefits


- Lightweight body
- Simple appearance
- Easy installation

Variants and dimensions



Model	Size (mm)			Colour body	Catalogue number	Packing (pcs)
	Diameter	Height	Diameter 1			
GL 210	228	110	210	white	9299210P/W	12
GL 210	228	110	210	satin nickel	9299210P/SN	12

Energy efficiency



Barcodes

Barcode	Catalogue number
3800131162755	9299210P/W
3800131162762	9299210P/SN

Standards

EN 60598-1

EN 60598-2-2

