

Attestation of Conformity

No. E8AUK 086470 0092 Rev. 00

Holder of Certificate: **Ginlong Technologies Co., Ltd.**
No.57 Jintong Road
Binhai Industrial Park, Xiangshan
315712 Ningbo, Zhejiang
PEOPLE'S REPUBLIC OF CHINA

Name of Object: **Converter**
(PV Grid-Tied Inverter)

This Attestation of Conformity is issued on a voluntary basis according to the Electromagnetic Compatibility Regulations 2016 relating to electromagnetic compatibility. It confirms that the listed apparatus complies with all essential requirements of the regulation and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: www.tuvsud.com/ps-cert

Test report no.: 64772218005801UK

Date, 2021-12-13




(Peter Jia)

Attestation of Conformity

No. E8AUK 086470 0092 Rev. 00

Model(s): Solis-1P2.5K-4G, Solis-1P3K-4G, Solis-1P3.6K-4G, Solis-1P4K-4G, Solis-1P4.6K-4G, Solis-1P5K-4G, Solis-1P6K-4G, S6-GR1P2.5K, S6-GR1P3K, S6-GR1P3.6K, S6-GR1P4K, S6-GR1P4.6K, S6-GR1P5K, S6-GR1P6K

Trade name: solis


Description of Object:

Models	Solis-1P2.5K-4G	Solis-1P3K-4G	Solis-1P3.6K-4G	Solis-1P4K-4G
PV input ratings:				
Max. input voltage:	550Vd.c.	600Vd.c.	600Vd.c.	600Vd.c.
MPP voltage range:	50-450Vd.c.	90-520Vd.c.	90-520Vd.c.	90-520Vd.c.
Max. input current:	2 x 11Ad.c.	2 x 11Ad.c.	2 x 11Ad.c.	2 x 11Ad.c.
Isc PV (absolute maximum):	2 x 17.2Ad.c.	2 x 17.2Ad.c.	2 x 17.2Ad.c.	2 x 17.2Ad.c.
AC output ratings:				
Rated grid voltage:	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.
Rated grid frequency:	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Rated output power:	2500W	3000W	3600W	4000W
Max. AC output active power:	2800W	3300W	4000W	4400W
Max. AC output apparent power:	2800VA	3300VA	4000VA	4400VA
Max. continuous output current:	13.3Aa.c.	15.7Aa.c.	16Aa.c.	21Aa.c.

Models	Solis-1P4.6K-4G	Solis-1P5K-4G	Solis-1P6K-4G
PV input ratings:			
Max. input voltage:	600Vd.c.	600Vd.c.	600Vd.c.
MPP voltage range:	90-520Vd.c.	90-520Vd.c.	90-520Vd.c.
Max. input current:	2 x 11Ad.c.	2 x 11Ad.c.	2 x 11Ad.c.
Isc PV (absolute maximum):	2 x 17.2Ad.c.	2 x 17.2Ad.c.	2 x 17.2Ad.c.
AC output ratings:			

Page 2 of 4

After preparation of the necessary UK regulation technical documentation as well as the UK declaration of conformity the required UKCA marking can be affixed on the product. Other applicable UK regulations have to be observed.

Attestation of Conformity

No. E8AUK 086470 0092 Rev. 00

Rated grid voltage:	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.
Rated grid frequency:	50/60Hz	50/60Hz	50/60Hz
Rated output power:	4600W	5000W	6000W
Max. AC output active power:	5000W	5000W	6000W
Max. AC output apparent power:	5000VA	5000VA	6000VA
Max. continuous output current:	23.8Aa.c	25Aa.c	27.3Aa.c.

Models	S6-GR1P2.5K	S6-GR1P3K	S6-GR1P3.6K	S6-GR1P4K
PV input ratings:				
Max. input voltage:	550Vd.c.	600Vd.c.	600Vd.c.	600Vd.c.
MPP voltage range:	50-450Vd.c.	90-520Vd.c.	90-520Vd.c.	90-520Vd.c.
Max. input current:	2 x 14Ad.c.	2 x 14Ad.c.	2 x 14Ad.c.	2 x 14Ad.c.
Isc PV (absolute maximum):	2 x 22Ad.c.	2 x 22Ad.c.	2 x 22Ad.c.	2 x 22Ad.c.
AC output ratings:				
Rated grid voltage:	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.
Rated grid frequency:	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Rated output power:	2500W	3000W	3600W	4000W
Max. AC output active power:	2800W	3300W	4000W	4400W
Max. AC output apparent power:	2800VA	3300VA	4000VA	4400VA
Max. continuous output current:	13.3Aa.c.	15.7Aa.c.	16Aa.c.	21Aa.c.

Models	S6-GR1P4.6K	S6-GR1P5K	S6-GR1P6K
Max. input voltage:	600Vd.c.	600Vd.c.	600Vd.c.
MPP voltage range:	90-520Vd.c.	90-520Vd.c.	90-520Vd.c.
Max. input current:	2 x 14Ad.c.	2 x 14Ad.c.	2 x 14Ad.c.
Isc PV (absolute maximum):	2 x 22Ad.c.	2 x 22Ad.c.	2 x 22Ad.c.
Rated grid voltage:	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.
Rated grid frequency:	50/60Hz	50/60Hz	50/60Hz

Page 3 of 4

After preparation of the necessary UK regulation technical documentation as well as the UK declaration of conformity the required UKCA marking can be affixed on the product. Other applicable UK regulations have to be observed.

Attestation of Conformity

No. E8AUK 086470 0092 Rev. 00

Rated output power:	4600W	5000W	6000W
Max. AC output active power:	5000W	5000W	6000W
Max. AC output apparent power:	5000VA	5000VA	6000VA
Max. continuous output current:	23.8Aa.c.	25Aa.c.	27.3Aa.c.

General specifications:		
Models	S6 series moldes	all other models
Adjustable cos(φ)	-0.8...1...+0.8	
Protection class	I	
Degree of protection	IP66	IP65
Overvoltage category	II(PV), III(MAINS)	
Ambient temperature	-25°C ... +60°C	
Inverter topology	Non-isolated	

**Tested
according to:**

EN IEC 61000-6-1:2019
 EN IEC 61000-6-2:2019
 EN 61000-6-3:2007/A1:2011
 EN IEC 61000-6-4:2019